




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A43B 5/16, A43C 1/00, A43B 5/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/37782 (43) International Publication Date: 3 September 1998 (03.09.98)</p>
<p>(21) International Application Number: PCT/CA98/00154 (22) International Filing Date: 24 February 1998 (24.02.98) (30) Priority Data: 2,198,448 25 February 1997 (25.02.97) CA (71) Applicant (for all designated States except US): BAUER INC. [CA/CA]; Suite 600, 8000 Decarie Boulevard, Montreal, Quebec H4P 2S4 (CA). (72) Inventor; and (75) Inventor/Applicant (for US only): RACINE, Bertrand [CA/CA]; 303 Lacharité Avenue, LaSalle, Quebec H8P 2B9 (CA). (74) Agents: GEORGIEV, Stephan, P. et al.; Smart & Biggar, Suite 3400, 1000 de la Gauchetière Street West, Montreal, Quebec H3B 4W5 (CA).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: ROLLER SKATE BOOT LACING SYSTEM

(57) Abstract

A skate boot comprising an outer shell and an inner liner, said shell and liner being provided with an opening generally adapted to substantially correspond at least partially with a portion of the dorsal area of the foot of the wearer, said liner and said shell being provided with attachment means for engagement with a lace, said attachment means being disposed such that at least a pair of said attachment means of said shell is disposed adjacent a pair of said attachment means of said liner to form an alternate lacing arrangement.



1/3




Fig. 1





Fig. 2

2/3

**Fig.3**

3/3




Fig. 4




Fig. 5




Fig. 6